

# \*PEST CONTROL INSPECTIONLIGHT

The most powerful UV-A & White Flashlight



## DUAL II POWERLIGHT

User friendly flashlight, used for UV-A visualisation as well as a regular white light flashlight.

Recommended for heavy duty use by professionals.

- Peak emission: 365 nm +/- 5 nm
- Charging via USB 3 connection or battery loader (separate available)

















## DUAL II POWERLIGHT

#### The most powerful UV-A & White Flashlight

Ultraviolet light is well known for their ability to visualize traces or items in several market segments Pest controllers, cleaning technicians, health inspectors, lab staff, metal industry.

Under influence of the right UV light (and in the right strength) a service technician can clearly identify these traces. Based on this the right follow up steps can be taken to effectively control them.

UV flashlights have been on the market for some time, but often the wrong wavelength were emitted and or the light was simply not strong enough.

These issues have been addressed with the new Dual II PowerLight from Alcochem Hygiene. A special UV-A/White LED has been developed, which combines strength and efficiency. 5 watts of concentrated UV-A light is at your disposal, which makes this flashlight the perfect tool for operational use in dimmed areas, but also for use in daylight areas.

The Dual II PowerLight comes in a professional Aluminium hard-anodized abrasive finish housing, is water proof and shock resistant.

Moreover, the Dual II PowerLight comes with a rechargeable battery and charger, which guarantees low operational costs and a long lifetime.

And ofcourse the emitted UV light is perfectly safe to use.



#### Technical specifications

Power LED's 1x 5 Watt UV-A 365 nm i.c.w. 1x 5 Watt white LED (300 Lumen)

Material Aluminum T6061, Premium Type III hard anodized abrasive finish

1x 18650 Li-ion rechargeable battery from Panasonic, 3400 mAh

Operational hours 3 hours\*
Lifetime LED's 20.000 hours

Tested drop height 1,2 m Color Black

Electrical supply charger 100-240 V - 50-60 Hz

Dimensions  $150 \times 27 \text{ mm (L} \times D (41 \text{ mm head)}$ 

Weight 184 Gram (incl batteries)
Handling Full grip, anti drop design

Belt holster Included

Carrying strap Included in the box

Reflector High temp, vacuum coated diffusor

Modes 4 softtouch modes (2x white and 2x UV-A)

Finishing Grade 3 compatible

IP rating IP67

Switch Metal executed button Standards CE & RoHS compliant

Quality procedure ISO 9001

Life span Min. 5 years

Certificate IEC report (IEC 60598-2-8) included

Manual Included in English language
Guarantee 2 years on electrical performance

\* Operational hours given are based on 2 hours use in white led position and 1 hour use in UV position.



### Intensity graph UV-A Light (365 nm)



